



7X1 Pump Combiner For DCF Output

DK Photonics' 7X1 Multimode Pump Combiner is designed for high power applications. It features exceptional optical characteristics. These devices can be used to combine the power from several multimode laser diodes, delivering the combined power for applications in industrial, military, medical and telecommunications markets. It has a heat sink package and a hole for temperature monitoring.

DK Photonics' Multimode Combiners offer efficient power transfer for high power applications like direct diode materials processing and pump cascading with a maximum conservation of brightness. The Multimode Combiners can be designed to meet a wide range of power handling configurations, number of input fibers and adaptation to different fiber types.

Features

- ◆ High Power Transfer Efficiency
- ◆ Low signal insertion loss
- ◆ Custom Configurations Available
- ◆ Wavelength Insensitive

Applications

- ◆ Fiber Laser Combination



Performance Specifications

Parameters	Value		
Product Code	MPC0701001	MPC0701002	MPC0701003
Pump Operating Wavelengths	800-1000nm	800-1000nm	800-1000nm
Number of Multimode Inputs	7	7	7
Number of Output Ports	1	1	1
Pump Input Fiber			
Core/clad diameter	105/125um	105/125um	200/220um
NA	0.22	0.22	0.22
Output Fiber			
Core/clad diameter	125um	20/400um	20/400um
NA	0.46	0.06/0.46	0.06/0.46
Insertion Loss	<0.5dB	<0.3dB	<0.3dB
Total Power	280W	700W	700W
Power per Multimode Input	40W	100W	100W
Optical Return Loss - Pumps	45dB	45dB	45dB
Multimode Power Transfer	>90%	>92%	>92%
Mechanical Specifications			
Dimensions	70x12x8(mm)		
Fiber Pigtail Length Input/Output	A: 1000mm; B: 2000mm; C: 3000mm		

* Pricing is dependent on fiber pigtail length.
**Specifications may be change without notice.

Order information:

MPC0701001A/B/C
.....

Package Information

Package Type	T1	T2	T3	T4	T5
Dimensions (Φ×L) (mm)	50×5×5	Φ4.0×60	70×12×8-3.5	70×12×8-5	105×11×7