



1080nm Cladding Power Stripper



Features

- ◆ High power handling
- ◆ Low Insertion loss
- ◆ Water-cooling
- ◆ Cost Effective

Applications

- ◆ Fiber Laser

Performance Specifications

Parameters	Values
Center Wavelength(nm)	1080
Operating Wavelength-Pumps (nm)	800~1200
Cladding attenuation(min)(dB)	20
Max. Insertion Loss (at 25°C) (dB)	0.30
Min. Polarization Extinction Ratio (dB)	15(For PM Fiber)
Cladding Power Handling(W)	20, 50, 100, 200
Fiber Type In/Out	20/250,25/250,20/400 DCF or Specify
Dimension(mm)	200x26.5x14.5
Water Pipe Type(mm)	4-6
Pigtail Length(m)	1.0 or other
Operation Temperature(°C)	0 ~ +50
Storage Temperature Range(°C)	-20 ~ +75

Order information

①①	②②	③③	④④	⑤⑤
wavelength	Cladding Power Handling	Fiber Type	Fiber Jacket on Input & Output	Fiber Length
80:1080nm XX:Other	20:20W 50:30W 100:100W XX:Other	01:20/250DCF Fiber 02:25/250DCF Fiber 03:20/400DCF Fiber P1:PM 10/125DCF Fiber XX:Other	B:Bare Fiber L:900um Loose Cable C:3MM Loose Cables X: Others	10:1.0m XX:Other

